

# STONELOK™ "MLT Plus"

## סילר מעולה על בסיס מים

לשטחים מרוצפים, בטון ומערכות צמנטיות

- תכולה נמוכה של רכיבים אורגניים נדיפים (V.O.C.), 80 גרם/ליטר: על בסיס מים, ללא ריחות דוחים וללא ממסים נדיפים.
- החומרים דוחים מים ודוחים שמן, בעלי עמידות גבוהה בפני שמנים, חומצות, ממסים, אלכוהולים ומלחים. עמידות מוחלטת בעת טבילה בטולואן למשך שעה אחת ול-100 שפופים הלוך וחזור במתיל-אתיל-קטון. לחות אינה גורמת חלודה או שלפוחיות [ASTM D610] וגם ריסוס ערפל-מלה אינו יוצר חלודה או שלפוחיות [ASTM D714].
- עמידות גבוהה: מבחן חיכוך במכשיר טאבור לאחר הקרשה - אובדן חומר של כ-50 מ"ג [ASTM D4060]. החוזק במתיחה: 45 מגפ"ס [ASTM D412].
- נוחים לניקוי: חומרי ניקוי אינם מסלקים את חומרי האטימה.
- מניעת התקלפות והתפוררות: קשיות Sward לאחר הקרשה: 48 לפחות.
- אינם מצהיבים ואינם דוחים אפילו באור שמש: לא חל שינוי במראה לאחר חשיפה לקרינה אולטרה-סגולה למשך 90 יום [WSTM C1378].
- מניעת החלקה נשמרת ואפילו משתפרת: החומרים עומדים או עולים על דרישת תקן ADA של ערך 0.6 [ASTM C1028].
- אפשרות צביעה ושיקום צבע בעזרת צבענים נוספים: ניתן להוסיף צבענים קולואידיים מסדרת RJSC S-Type™, רגילים או בהזמנה מיוחדת, לשם גיוון או שינוי צבע.

StoneLok™ "MLT Plus" הינו סילר פוליאוריטני המורכב מחלקיקים זעירים של פולימרים המעניקים כושר התפשטות וזרימה מעולה, אחידות חזירה והגנה.

הקשר הכימי ("נעילה") של שרפי StoneLok מצע (ו/או לפריימר המומלץ) הוא תמידי כדי להבטיח יציבות ועמידות לאורך זמן.

StoneLok™ "MLT Plus" חדיר לאדים כדי לאפשר למצע "לנשום" ללא סכנת הפרדת שכבות או קריסה. StoneLok™ "MLT Plus" מיועד לשימוש פנימי וחיצוני כאחד וכמעט שאינו גורם להבלטה של צבע המצע.

העמידות בשחיקה ובכימיקלים של StoneLok™ "MLT Plus" מוכחת במרכזי תחבורה ראשיים ובמספר מוזיאונים בהם הדרישות הגבוהות ביותר מתפקוד המערכת.

על גבי מצע נקבובי יש ליישם את החומרים במברשת, ברולר או במרסס HVLP (מכשיר ריסוס הפועל במהירות גבוהה ובלחץ נמוך). על מצע חלק או על גבי פריימר חובה להשתמש במרסס HVLP. מיישמים מיומנים יכולים גם להשתמש במרסס מסוג AIRLESS (מכשיר ריסוס ללא לחץ אוויר).

כושר הכיסוי נע בטווחים של 28 מ"ר ועד 60 מ"ר לגלון, בכפוף לסוג המצע, בשכבה שניה יהיה הכיסוי לרוב כ-46 מ"ר לגלון.

StoneLok™ "MLT Plus" מיועד ליישום על משטחי גרניט מלוטש, אריחי אבן, צפחה, אריחי קרמיקה, אבן-חול, ריצוף מדרכות ובטון. עבור טראצו פתוח, אבן גיר מלוטשת וכן אגרגט של פחמת הסידן יש ליישם לאחר טיפול ב-O-S™ או ב-AMS™.

StoneLok™ "MLT Plus" הינו ציפוי מושלם על גבי או כחיפוי עליון על גבי RJSC TekSeal™ או TekSeal PRO, פריימר אפוקסי מסדרת 200™ או StoneLok™ "E3" כאשר נדרש גימור מאט. זמין בגימור מאט, מבריק במקצת ומבריק.



סנוקרטי (1992) בע"מ

לסיוע טכני ניתן לפנות:

סנוקרטי (1992) בע"מ

נחל בוקק 6, מודיעין 71704

טלפון: 972-8-9702384 פקס: 972-8-9702385

דוא"ל: [contact@frp.co.il](mailto:contact@frp.co.il) אתר: [www.frp.co.il](http://www.frp.co.il)

**RICHARD JAMES**  
**Specialty Chemicals Corp.**  
24 Ridge Street • Hastings-on-Hudson, NY 10706  
(914) 478-7500 Fax: (914) 478-7516 [www.rjsonline.com](http://www.rjsonline.com)

### SUBJECT TO RJSC MSDS AND LIMITED WARRANTY

**Limited Warranty:** The products of Richard James Specialty Chemicals Corporation (RJSC) contain highest quality raw materials and are manufactured under strict conditions of quality control. RJSC cleaners are warranted to conform to manufacturing specifications for a period of one year from initial delivery when stored in conditions greater than 32° F. and below 90° F. RJSC primers, sealers, Colloidal Dyes, primers and sealers with incorporated Colloidal Dyes, and floor finishes are warranted to conform to the manufacturing specifications for a period of six months from initial delivery when stored in conditions greater than 32° F and below 90° F. No warranty or affirmation of fact, express or implied, other than as set forth in this limited warranty is made by RJSC regarding its product(s). This limited warranty only applies to products purchased directly from RJSC. RJSC expressly disclaims all express and/or implied warranties for its product(s) that are not purchased directly from RJSC or are resold to or by third parties.

Due to the possibility of improper application, adverse surface or climatic conditions beyond our control, users of RJSC products shall make their own determinations, based on their own tests, as to the suitability of the product(s) for the intended purposes. RJSC hereby expressly disclaims any liability for claims that are due to product misuse, improper product selection, misapplication of product(s), substrate selection and preparation, environmental conditions and any failure to observe safety precautions. RJSC hereby disclaims any implied warranties of merchantability or fitness for any particular purpose regarding any product.

RJSC shall have no liability for consequential, incidental and/or special damages regarding the sale or use of a product even if the potential for such damages has been disclosed to Richard James Specialty Chemicals Corporation. RJSC's liability for product claims is limited to only replacement, at the option of RJSC or refund of the purchase price of the product applied per most current published directions. RJSC's liability shall not exceed the purchase price paid for the product and shall not include any special incidental or consequential losses or damages resulting from selection, use, installation, handling, care of or replacement of the product(s). The limited warranty does not include labor or the cost of labor for application.

Should a claim be asserted against RJSC by any party who did not purchase products directly from RJSC, RJSC shall be indemnified and held harmless by the party who did purchase the products directly from RJSC, including the reasonable attorneys' fees, costs and disbursements incurred by RJSC in its defense of any said claim. This indemnification shall not be deemed or in any manner expand or create a greater obligation on the part of RJSC than that set forth in this Limited Warranty.

This StoneLok formulation and others for projects with higher protection requirements and/or for unique substrates or special environmental/installation conditions are available through select contractors and some Distributors. To locate the source closest to you, please contact Richard James Specialty Chemicals directly.

StoneLok, TekSeal, S-Type, 200-Series, O-S and AMS are trademarks of Richard James Specialty Chemicals Corp. Hastings, NY